

WELDING DIRECT.co.nz



The WDMIG200M is an inverter-based portable MIG welding machine with added MMA and DC TIG function providing excellent, professional welding results. The MIG function allows you to weld with both Gas Shielded and Gasless wires. Connection of the WP17 TIG torch provides simple but professional H/F DC TIG welding of steel, stainless steel and copper. An additional feature is the Spoolgun function that allows for the use of thin or softer wires that don't have the column strength to feed through standard MIG torches, such as aluminium wire.

MODEL	140Ms						200Ms						MIG140Msv						MIG200Msv																	
Power Supply Voltage(V)	1P~220/230/240±15%												1P~110/115/120/220/230/240±15%																							
Frequency(HZ)													50/60																							
	220						110						220						110						220											
	MIG	MMA	TIG	MIG	MMA	TIG	MIG	MMA	TIG	MIG	MMA	TIG	MIG	MMA	TIG	MIG	MMA	TIG	MIG	MMA	TIG															
Reted Input Power(KW)	3.7	4.7	2.9	6.0	6.6	4.1	3.0	3.7	2.2	3.7	4.7	2.9	3.7	4.5	2.7	6.0	6.6	4.1																		
Reted Input Current(A)	22.8	28.0	17.0	37.4	40.8	26.0	37.4	46.3	26.0	22.8	28.0	17.0	45.7	55.9	34.0	37.4	40.8	26.0																		
Duty Cycle(40°C 10min)	60%140A						60%190A						60%120A						60%140A						60%140A						60%190A					
	100%108A						100%147A						100%93A						100%108A						100%108A						100%147A					
No Load Voltage(V)	56						56						56						56						56											
Welding Current Range(A)	30~140	10~140	10~140	30~200	10~190	10~190	30~120	10~120	10~120	30~140	10~140	10~140	30~140	10~140	10~140	30~200	10~190	10~190																		
Welding Voltage Range(V)							14~20			14~21			14~21			14~24			14~24																	
Efficiency(%)													≥80																							
Power Factor													0.73																							
Protection Class													Ip23																							
Insulation Class													H																							
Cooling													AF																							
Wire Diameter(mm)	0.6~0.9						0.6~1.0						0.6~0.9						0.6~1.0						0.6~0.9						0.6~1.0					
Net Weight(kg)	16						17.7						16.5												18.2											
Gross Weight(kg)	19						20.7						19.5												21.2											
Dimensions(mm)													655×325×455																							

Optional trolley available



Multimig pursue a policy of continuous research and development, and therefore reserve the right to change the specifications, or design, without prior notice

1 year warranty power source